



CAT 930M

SMALL WHEEL LOADER



- Intelligent Power Management
- Optimized Z-bar Linkage
- Quick Loading Performance Series Bucket
- Smooth and Predictable Multi-Function Performance
- Superior All Around Visibility
- Spacious, Safe, Quiet Operator Environment
- Bucket and Fork Tines

Maison Concrete Placement Systems
949 Sumner Ave, Whitehall, PA 18052
Phone: (610) 821-1325 Fax: (610) 821-1326
www.maisonpumping.com





CAT 930M

SMALL WHEEL LOADER

PRODUCT SPECIFICATIONS

ENGINE

Maximum Gross Power	164.0 hp
Bore	4.0 in
Stroke	5.0 in
Displacement	427.0 in ³
Rated Net Power	157.0 hp
Engine Model	Cat® C7.1 ACERT™
Maximum Rated Gross Power: ISO 14396	164.0 hp
Maximum Rated Gross Power: ISO 14396 (DIN)	166.0 hp

BUCKETS

Bucket Capacities	2.1-5.0 m ³ (2.7-6.5 yd ³)
-------------------	---

WEIGHTS

Operating Weight	30879.0 lb
------------------	------------

STEERING

Steering Cylinder: Double Acting – Bore Diameter	2.8 in
Steering Cylinder: Double Acting – Rod Diameter	1.6 in
Steering Cylinder: Double Acting – Stroke	17.2 in
Maximum Flow – Steering Pump	34.0 gal/min
Maximum Working Pressure – Steering Pump	3500.0 psi
Maximum Steering Torque – 0° (Straight Machine)	37155.0 lbf-ft
Maximum Steering Torque – 40° (Full Turn)	27747.0 lbf-ft

LOADER HYDRAULIC SYSTEM

Maximum Flow – Implement Pump	50.0 gal/min
Maximum Working Pressure – Implement Pump	3626.0 psi
Relief Pressure – Tilt Cylinder	4061.0 psi
Lift Cylinder: Double Acting – Bore Diameter	4.7 in
Lift Cylinder: Double Acting – Stroke	28.7 in
Tilt Cylinder: Double Acting – Bore Diameter	5.9 in
Tilt Cylinder: Double Acting – Rod Diameter	3.5 in
Tilt Cylinder: Double Acting – Stroke	21.9 in

SERVICE REFILL CAPACITIES

Fuel Tank	51.5 gal
Cooling System	7.9 gal

Maison Concrete Placement Systems
949 Sumner Ave, Whitehall, PA 18052
Phone: (610) 821-1325 Fax: (610) 821-1326
www.maisonpumping.com

