



CAT TL1255C

TELEHANDLER



- Improved Job Site Visibility and Easy to Use Controls
- Comfortable and Efficient Joystick for Ease of Operation
- 54.3' (16.6m) Maximum Lift Height
- Three Steering Modes: Two Wheel, Crab and 4-Wheel
- Load Capacity of 12,000 lbs. (5400kg)
- Cat C4.4 ACERT Tier 4 Interim Engine
- ZF, WG98-TSC Power-Shift Transmission

Maison Concrete Placement Systems
949 Sumner Ave, Whitehall, PA 18052
Phone: (610) 821-1325 Fax: (610) 821-1326
www.maisonpumping.com





CAT TL1255C

TELEHANDLER

PRODUCT SPECIFICATIONS

ENGINE

Engine Model Cat® C4.4 ACERT™, Tier 4 Interim
Gross Power (Basic) 142.1 hp

WEIGHTS

Operating Weight 35860.0 lb

OPERATING SPECIFICATIONS

Rated Load Capacity 12000.0 lb
Maximum Lift Height 54.3 ft
Load at Max Height - Stabilizers Down 5000.0 lb
Load at Max Height - Stabilizers Up 4000.0 lb
Maximum Forward Reach 42.5 ft
Load at Max Reach - Stabilizers Down 3500.0 lb
Top Travel Speed 20.4 mph
Load at Max Height 5000.0 lb
Load at Max Reach 3498.73 lb

DIMENSIONS

Height 8.4 ft
Width 8.4 ft
Wheelbase 12.0 ft
Length to Fork Face 20.8 ft
Ground Clearance 19.0 in
Turning Radius Over Tires 14.0 ft

BOOM PERFORMANCE

Boom Up 16.0 Seconds
Boom Down 14.8 Seconds
Tele In 13.4 Seconds
Tele Out 17.2 Seconds
Drawbar Pull (Basic) 20000.0 lb

OPERATOR STATION

Features Vinyl suspension seat, single electronic joystick, spacious interior, ergonomic cab

Maison Concrete Placement Systems
949 Sumner Ave, Whitehall, PA 18052
Phone: (610) 821-1325 Fax: (610) 821-1326
www.maisonpumping.com

